

## FLASH TAPE

This flash tape has only one single side.

This special tape is resisting to high temperature environment; it is commonly used in the composites industry (autoclave – thermocouple – Oven – Vacuum Bag).



### IDEAL FOR

- ✓ Thermocouples
- ✓ Autoclave
- ✓ Oven
- ✓ Hot Bonder

### SPECIFICATIONS & FEATURES

- ✓ Quantity : 1 flash tape
- ✓ Single side
- ✓ Max temp : depends of the product

Flash Tapes					
Part Number	Temp.	Length	Adhesive support	Color	Use
A8BFTK0107	204°C – 399°F	66M	Polyester / Acrylic	Yellow	High Temp.
A8BFTK7666	204°C – 399°F	66M	Polyester / Silicon	Blue	Standard
A8BFTPTFE02	260°C – 500°F	66M	PTFE / Silicon	Grey	High Temp.
A8BFTK7338	300°C – 572°F	33M	Polyimide / Silicon	Orange	Very High Temp.
A8BFTK6337	300°C – 572°F	33M	Polyimide / Acrylic	Orange	Very High Temp.

## KEYBOARD

Ref. : A11KBQW01 (QWERTY)

Ref. : A11KBAZ01 (AZERTY)

This silicon Keyboard is ideal to control your Hot Bonder.

With its flexibility, it will allow you to work in the best condition.



### IDEAL FOR

- ✓ Hot Bonder

### SPECIFICATIONS & FEATURES

- ✓ USB
- ✓ PS/2
- ✓ Flexible
- ✓ Seal
- ✓ AZERTY / QWERTY (on demand)

## ACCESSORY CASE EMPTY

This is an accessory case empty to carry your material.

### Accessory Case Empty

Part Number	Weight of the empty box	Size	Use	Product
A8ACESZ	2.5Kg	430 x 380 x 154 mm	Hot Bonder	
A8ACEDZ	4.8Kg	524 x 428 x 206 mm		