

MOVABLE DOWNDRAFT TABLE

A9DTM

MOVABLE DOWNDRAFT TABLE A9DTM

The movable downdraft table A9DTM has been especially designed to capture dust, residues at the end of every sanding, deburring and dusting operation.

A capture rate greater than 0.5 m / s is assured thanks to the 2700 m³ / h flow rate. The purified air is evacuated from outside or through a HEPA H13 filter.

In case of filter wear, the differential pressure switches transmit the information by a light on the control unit.

A good suction distribution is guaranteed thanks to the removable lateral protections on hinges, which allows the loading and the unloading, even a punctual lateral work.



Foldable downdraft table

IDEAL FOR

- ✓ Multi-site transportation
- ✓ Carbon part repair
- ✓ Dust capture of composite materials

MAIN FEATURES

- ✓ Low noise level: ≤ 70 dB
- ✓ Movement and blocking wheels
- ✓ Movable lateral protections
- ✓ ATEX construction
- ✓ Opacimetric filter F7
- ✓ Absolute filter HEPA H13, 99,95%
- ✓ « Light Duty »
- ✓ Polyethylene worktop (non scratching)

Reference		Material		Worktop*			
A9DTM1000	1105x1010	Steel	210 kg	660x690	1600m ³ /h	0,75 kW	220 V Tri

*D x L