# **VACUUM PLUG**

# A5QEVPD60

### DESCRIPTION

Manufactured from aluminum, the A5QEVPD Aeroform vacuum plug is composed of 2 pieces. The upper part is associated with the lower part by a simple rotation ¼ turn.

A silicone seal placed between the two parts, ensures the sealing of your vacuum.

This vacuum plug is used in high temperature enclosures up to 230 ° C.

A QRC (Quick Release Coupling) ¼ gas can be provided with the vacuum plug \*.

\*upon request



### IDEAL FOR

- ✓ Autoclave
- ✓ Oven

#### ADVANTAGES

- ✓ Quick to set up
- ✓ Quick tightening by turning ¼ turn

### **TECHNICAL INFORMATION**

✓ Base: 60 mm in diameter

✓ Thread: ¼ gas

✓ Using temperature: 230°C

### **OPTION**

✓ Connector

#### References with QRC

	References			(~)	Material		Information
Sanoesca	A5QEVP	60mm	210°C	5Bars	Aluminium	1/4	QRC Brass
	A5QEVPX	60mm	230°C	5Bars	Aluminium	1/4	QRC Stainless Steel



# **VACUUM PLUG**

# A5QVPD65

# **DESCRIPTION**

This Aeroform A5QPD65 vacuum plug is composed of 2 pieces. The upper part perforates the vacuum bag when it is positioned on the base.

A silicone seal placed between the two parts ensures the tightness of your vacuum.

This vacuum plug is used in high temperature enclosures up to 230 ° C.

A QRC (Quick Release Coupling) 1/4 gas can be provided with the vacuum plug \*.

\*upon request



### IDEAL FOR

- ✓ Autoclave
- ✓ Oven

#### ADVANTAGES

- ✓ Simple to set up
- Secure tightening
- ✓ Tightness ensured by screwing
- √ Vacuum bag self-perforation

### **TECHNICAL INFORMATION**

✓ Base: 65 mm in diameter

✓ Thread: 1/4 gas

√ Using temperature: 230°C

### **OPTION**

✓ Connector

#### References for QRC

References	$\overline{\longleftrightarrow}$		(~)	Material		Information
A5QVP	65mm	210°C	10Bars	Aluminium	1/4	QRC Brass
A5QVPX	65mm	230°C	10Bars	Aluminium	1/4	QRC Stainless Steel



# **VACUUM PLUG**

# A5QVPSD50

### **DESCRIPTION**

This Aeroform A5QVPSD50 vacuum plug is composed of 2 pieces.

A silicone seal placed between the two parts ensures the tightness of your vacuum.

This vacuum plug is used in high temperature enclosures up to 230 ° C.

A QRC (Quick Release Coupling) 1/4 gas can be provided with the vacuum plug \*.

\*upon request



#### **IDEAL FOR**

- ✓ Autoclave
- ✓ Oven
- ✓ Hot Bonder

#### ADVANTAGES

- ✓ Easy to set up
- ✓ Simple and economical design
- ✓ Tightness ensured by screwing
- ✓ Secure tightening

### **TECHNICAL INFORMATION**

✓ Base: 50 mm in diameter

√ Thread: 1/4 gas

✓ Using temperature: 230°

### **OPTION**

✓ Connector

#### References with QRCs

References	$\overline{\longleftrightarrow}$		( <b>?</b> )	Material		Information
A5QVPS	50mm	210°C	10Bars	Steel	1/4	QRC Brass
A5QVPSX	50mm	230°C	10Bars	Steel	1/4	QRC Stainless Steel

